

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
12 February 2004 (12.02.2004)

PCT

(10) International Publication Number
WO 2004/012908 A1

(51) International Patent Classification⁷: B25B 15/00,
F16B 31/02, 23/00, 41/00

(21) International Application Number:
PCT/IL2003/000611

(22) International Filing Date: 24 July 2003 (24.07.2003)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
151060 4 August 2002 (04.08.2002) IL

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

(71) Applicant and

(72) Inventor: AVGANIM, Mair [IL/IL]; 156 Moshav Gealiya, 76885 M.P. Nachal Sorek (IL).


(74) Agent: FREIMANN, Daniel; P.O.Box 29814, 61297 Tel-Aviv (IL).

Published:

— with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: AUTO-TORQUE, TAMPER-PROOF SCREWS



(57) Abstract: A screw (10) having a screw-threaded shank (14) and a circular head (12), the head being provided with three radially extending screwdriver tip receiving portions (16; 18; 20) defined between three first, off-central integrally formed projections (16a; 18a; 20a) designed to become shaved-off the screw head by a pre-set shear force applied during tightening of the screw, and three second, integrally formed projections (16c; 18c; 20c) designed to withstand a shear force greater than the said pre-set force applied during slackening of the screw.